



Lapp Group offers a complete cable trolley system both for flat cables and for round cables.

- Our configuration tool on our homepage (Knowledge center-cable accessories) supports you in choosing the correct cable trolley system
- 3D drawings available

Product description

Application range

- Crane and conveying machinery
- For hoisting equipment and conveyor systems
- Mechanical engineering
- Not suitable for applications for Ex-Areas

Benefits

- The guiding rollers have ball bearings and guarantee easy, smooth running in the C-profile rails.
- The cables in the clamping devices are clamped gently, and an appropriately shaped pressing piece prevents sharp bends at the clamping point.

Product Make-up

- Complete system consisting of the following components:
 1. Clamps (steel girder)
 2. Extension arm
 3. End clamp
 4. Rail bracket
 5. Stopper

6. Cable trailer
7. Track coupler
8. C-profile rail
9. Towing arm
10. Towing trolley

Product Make-up

- The delivery length of the C-profile rail is 6 m.
- The rail opening is 11 mm
- The installation of a system depends on various criteria, e.g. maximum cable slack (cable weight) and working length.

Note

- Round- and flat cables are not allowed to combine a sight below and above

Product features

- Certain components (such as the cable trailer) made of galvanised steel
- Dustproof ball bearing (wheels)
- Cable clamp and protection plate made of polyamide

Technical Data

General
Temperature range

Max. cable load: 20 kg
-40°C to +160°C