



Cable according ISOBUS standard (ISO 11783-2) for use in agricultural vehicles; HYBRID: cable for data transmission + power supply

- ISOBUS is a bus system for agricultural vehicles, which is standardized in the international standard ISO 11783-2
- Lapp cable is member of the AEF Agricultural Industry Electronics Foundation















Product description

Application range

- For outdoor applications
- Connection cable between tractor and pulled machinery

Benefits

- Cable according ISOBUS standard (ISO 11783-2) for use in agricultural vehicles.
- HYBRID: cable for data transmission + power supply

Product Make-up

4x 0,5 mm² (red, yellow, black, green)
2x 2,5 mm² (red, black)
2x 6 mm² (red, black)

UNITRONIC® BUS IS



- Fine-wired copper conductor of bare copper strands in line with conductor class 5 acc. IEC 60228
- Outer Sheath: Black PVC or PUR special compound

Norm references / Approvals

• ISO 11783-2:2012

Product features

- Flame-retardant according to IEC standard 60332-1
- Resistant against oil, benzine and diesel
- UV-resistant
- PUR (Polyurethane) Version with increased robustness, UV- resistance and halogen free

Technical Data

Peak operating voltage 60 V

Test voltage $0.5 \text{ mm} - 2.5 \text{ mm}^2 \text{ core} / \text{ core} = 1.5 \text{ kV}$

 $6 - 10 \text{ mm}^2 \text{ core} / \text{ core} = 2,5 \text{ kV}$ Temperature range $PUR: -40^{\circ}C \text{ to } +85^{\circ}C$

PUR: -40°C to +85°C PVC: -30°C to +85°C

Characteristic impedance: 75 ohm