



Suitable for outdoor use and direct burial, UV-resistant

Rugged, UV-resistant and weatherproof; Cables can be used for PROFIBUS-DP as well as PROFIBUS-FMS and FIP



Product description

Application range

- PROFIBUS DP (in accordance with DIN 19245 and EN 50170, e.g. for SIEMENS SIMATIC® NET, also suitable for FIP - Factory Instrumentation Protocol).

Benefits

- Rugged, UV-resistant and weatherproof
- Cables can be used for PROFIBUS-DP as well as PROFIBUS-FMS and FIP

Product Make-up

- Solid and bare copper conductor
- PE core insulation
- Overall screening with copper braid and plastic-laminated aluminium foil

- Tin-plated copper wire braiding
- PVC outer sheath, violet, OD 7.5 mm
PVC outer sheath, black, OD 9.5 mm

Product features

- Dual PVC outer sheath

Technical Data

Mutual capacitance	(800 Hz): max. 30 nF/km
Peak operating voltage	(not for power applications) 250 V
Minimum bending radius	Fixed installation: 75 mm once Fixed installation: 150 mm
Test voltage	Core/core: 1500 V rms Core/screen: 1500 V
Temperature range	Flexing: -5°C to +50°C Fixed installation: -40°C to +80°C
Characteristic impedance	150 ± 15 Ohm