



Screened data transmission cable with colour code acc. to DIN 47100

Overall braid minimises electrical interference; Multifunctional application possibilities



Product description

Application range

- Screened cables with small dimensions are suitable for use in computer systems, instrumentation technology, office equipment, balances.
- Dry or damp rooms

Benefits

- Overall braid minimises electrical interference
- Multifunctional application possibilities

Product Make-up

- Fine-wire/multi-wire (0.34 mm²) strand made of bare copper wires
- Core insulation made of PVC

- Tinned-copper braiding
- Outer sheath made of PVC
Outer sheath colour: pebble grey (RAL 7032)

Norm references / Approvals

- Based on VDE 0812

Product features

- Flame-retardant according IEC 60332-1-2

Technical Data

Core identification code	DIN 47100 without colour repetition, refer to Appendix T9
Mutual capacitance	C/C: approx. 120 nF/km C/S: approx. 160 nF/km
Peak operating voltage	(not for power applications) at 0.14 mm ² : 350 V at ? 0.25 mm ² : 500 V
Classification	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Inductivity	approx. 0.65 mH/km
Conductor stranding	Stranded, fine-wire 0.34 mm ² : 7-wire
Minimum bending radius	Occasional flexing: 15 x outer diameter Fixed installation: 6 x outer diameter
Test voltage	At 0.14 mm ² : 1200 V ? 0.25 mm ² : 1500 V
Temperature range	Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C