



## Data transmission cable with colour code acc. to DIN 47100

Space-saving installation due to small cable diameters; Multifunctional application possibilities; Depending on the quantity, the outer sheath can also be produced in other colours to match your application needs

- The classic for multi-functional use



## Product description

### Application range

- UNITRONIC® LiYY is also used as a control and signal cable in electronics of computer systems, electronic control equipment, office machines, balances, etc.
- Dry or damp rooms
- Occasional flexing

### Benefits

- Space-saving installation due to small cable diameters
- Multifunctional application possibilities
- Depending on the quantity, the outer sheath can also be produced in other colours to match your application needs

### Product Make-up

- Fine-wire/multi-wire (0.34 mm<sup>2</sup>) strand made of bare copper wires
- Core insulation made of PVC
- Outer sheath made of PVC  
Outer sheath colour: pebble grey (RAL 7032)

## Norm references / Approvals

- Based on VDE 0812

## Product features

- Despite the large number of cores, LiYY data cables have small outer diameters
- Flame-retardant according IEC 60332-1-2

## Technical Data

Core identification code	DIN 47100 without colour repetition, refer to Appendix T9
Mutual capacitance	Approx. 120 nF/km
Peak operating voltage	(not for power applications) at 0.14 mm <sup>2</sup> : 350 V at ? 0.25 mm <sup>2</sup> : 500 V
Classification	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Inductivity	approx. 0.65 mH/km
Conductor stranding	Stranded, fine-wire 0.34 mm <sup>2</sup> : 7-wire
Minimum bending radius	Occasional flexing: 10 x outer diameter Fixed installation: 4 x outer diameter
Test voltage	At 0.14 mm <sup>2</sup> : 1200 V ? 0.25 mm <sup>2</sup> : 1500 V
Temperature range	Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C