



## Halogen-free data transmission cable with colour code acc. to DIN 47100

Halogen-free: to protect human life and valuable assets in the event of a fire, through low smoke density and low amount of corrosive gases; Low capacitance due to polyolefin-based insulation; Small outer diameters despite a high number of cores

- For use within public buildings and industrial plants



## Product description

### Application range

- Suitable for areas with a high density of people as well as high-value property that must be protected in the event of a fire
- For use within public buildings, transport systems and industrial plants
- For data processing, measurement and control engineering, safety related systems and as electronics cable
- 7-wire stranded conductor can be used for Maxi TERMI-POINT® wiring (for this product the 0,34mm<sup>2</sup> version only)
- Dry or damp rooms

### Benefits

- Halogen-free: to protect human life and valuable assets in the event of a fire, through low smoke density and low amount of corrosive gases

- Low capacitance due to polyolefin-based insulation
- Small outer diameters despite a high number of cores

## Product Make-up

- Fine-wire/multi-wire (0.34 mm<sup>2</sup>) strand made of bare copper wires
- Core insulation made of special halogen-free compound
- Outer sheath made of special halogen-free compound  
Outer sheath colour: pebble grey (RAL 7032)

## Norm references / Approvals

- Based on VDE 0812

## Product features

- Flame-retardant according IEC 60332-1-2
- Low smoke zero halogen (LSZH)
- Halogen-free according to IEC 60754-1  
(amount of halogen acid gas)  
Corrosiveness of combustion gases according to EN 50267-2-3 (degree of acidity)
- Low smoke density according to IEC 61034-2

## Technical Data

Core identification code	DIN 47100 without colour repetition, refer to Appendix T9
Mutual capacitance	Approx. 80 nF/km
Peak operating voltage	(not for power applications) 250 V
Classification	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Inductivity	approx. 0.65 mH/km
Conductor stranding	Stranded, fine-wire 0.34 mm <sup>2</sup> : 7-wire
Minimum bending radius	Occasional flexing: 10 x outer diameter Fixed installation: 6 x outer diameter
Test voltage	1200 V
Temperature range	Occasional flexing: -5°C to +70°C Fixed installation: -30°C to +80°C