



Universal and easy to install AS-Interface distributor for data and power supply. Designs as H Distributor or with M12 connector.

- AS-Interface Adapter for data and power supply



Product description

Application range

- Automation technology
- Mechanical engineering
- Plant engineering
- Tool shop
- Automotive industry

Benefits

- Inexpensive and efficient wiring for AS-Interface installations
- Space-saving due to compact dimensions
- Easy to install
- Standardised interfaces

Product Make-up

- Fixed flexible control cable
- Design: 4 x 0.34 mm² (42 x 0.1 mm)
- Core colours: brown(1), white(2), blue(3), black(4)
- Outer sheath: PUR, halogen-free
- Outer sheath colour: black

Product features

- Passive AS-Interface distributor for 1 or 2 AS-Interface flat cables
- Distributor with integrated M12 socket (A-coded)
- H distributor for distribution from 1 to 2 flat cables
- Distributor with round cable and M12 socket (A-coded)
- Colour: black
- Rated current ? 4 A
(H-distributor: I ? 8 A)

Technical Data

| | |
|---------------------------------|--------------------------------------|
| Connection type | Penetration technique for flat cable |
| Fieldbus system | AS-Interface |
| Installation | Panel mounting |
| Protection rating | IP 67 (H-distributor: IP69k) |
| Ambient temperature (operation) | -25°C to +75°C |