



Shielder sensor/actuator cable in 3-, 4-, 5-pos. Versions, straight and angled M12 plugs and sockets

- Suitable for drag chains



Product description

Application range

- Automation technology
- Mechanical engineering
- Plant engineering
- Tool shop
- Automotive industry

Benefits

- Cost-saving due to quick and easy installation
- Space-saving due to compact dimensions
- Fast and easy error tracking
- Standardised interfaces

Product Make-up

- Fixed flexible control cable
- Design:
 - 3 x 0.34 mm² (42 x 0.1 mm)
 - 4 x 0.34 mm² (42 x 0.1 mm)
 - 5 x 0.34 mm² (42 x 0.1 mm)
- Outer sheath: PUR, halogen-free, screened
- Outer sheath colour: black
- Shielding is conducted over the knurl

Product features

- 3, 4 and 5-pin version
- Plug/socket with M12 thread to free conductor end
- The cables have marker carriers
- Free of paint-wetting impairment substances
- Suitable for drag chains

Technical Data

Coding	A-Standard
Gripping body material	TPU, flame-retardant, self-extinguishing
Contact surface material	Ni/Au
Contact material	CuSn
Knurl material	Zinc die-cast, nickel-plated
Protection rating	IP65/IP67
Ambient temperature (operation)	Plug/socket -25°C to +90°C Cable, fixed installation -25°C to +80°C Cable, flexible installation -5°C to +80°C