




Cost-saving due to quick and easy installation; Space-saving due to compact dimensions; Fast and easy error tracking; Standardised interfaces



Product description

Application range

- Automation technology
- Mechanical engineering
- Plant engineering
- Tool shop
- Automotive industry

Benefits

- Cost-saving due to quick and easy installation
- Space-saving due to compact dimensions
- Fast and easy error tracking
- Standardised interfaces

Product Make-up

- Cable design:
 - 3 x 0.5 mm² (28 x 0.15 mm)
 - 5 x 0.5 mm² (28 x 0,15mm)
- Core colours:
 - black 1, black 2, green/yellow
 - black 1, black 2, black 3, black 4, green/yellow
- Outer sheath: PUR, halogen-free
- Outer sheath colour: black (RAL 7021)
- Outer diameter:
 - 4.5 mm
 - 5.3 mm
- Suitable for drag chains

Product features

- 3- and 5-pin valve connectors
- With protective circuit (Z diode)
 - PE-bridged
 - Valve connector for pressure switches
- With LED status indicator (yellow)
 - With display switch state (2 LEDs, red/green)
- The cables have marker carriers
- Free of paint-wetting impairment substances

Technical Data

Coding	A-Standard
Contact surface material	Ag
Contact material	CuSn
Protection rating	IP 67
Ambient temperature (operation)	Valve connector -20°C to +85°C Cable, fixed installation -40°C to +80°C Cable, flexible installation -15°C to +80°C