




Single-pin circular connector for mobile power distribution, electro motors and generators

Resistant to mechanical influences in harsh environmental conditions; Connectors in harmonised colours according to European standards; Every colour has a different coding to prevent incorrect plugging



Product description

Application range

- For renewable energy plants e.g. wind power
- For mobile and stationary power distribution
- For the connection of motors, transformers and generators
- Light & sound technology

Benefits

- Resistant to mechanical influences in harsh environmental conditions
- Connectors in harmonised colours according to European standards
- Every colour has a different coding to prevent incorrect plugging

Product features

- Straight connector with M40 thread

- Order SKINTOP® ST-M 40 or STR-M 40 separately
- Contact fixing by contact retention pin, each pin can only be used once
- Housing without contact, order contact separately

Technical Data

Rated voltage (V)	1000 V
Rated impulse voltage	8 kV
Rated current (A)	Screw max. 400 A
Contacts	Screw termination: silver-plated brass
Number of contacts	1
Termination methods	Screw termination: 50 - 120 mm ²
Material	Housing: PBT Contact retention pin: PA
Protection rating	IP 67 (maximum, dependant on cable gland used) IP 20 (unmated)
Cycle of mechanical operation	500
Temperature range	-25°C ... +125°C
VDE-tested	VDE Reg. No. D42
Degree of soiling	3