



## These high-voltage inserts are additionally equipped with 2 switching contacts

With the relevant wiring, the lagging switch contacts interrupt the power supply before the working contacts are separated; These high-voltage inserts are additionally equipped with 2 switching contacts

- Multipole insert with lagging switch contacts
- Switching operations possible for disconnecting under load



## Product description

### Application range

- Mechanical engineering
- Plant engineering

### Benefits

- With the relevant wiring, the lagging switch contacts interrupt the power supply before the working contacts are separated
- These high-voltage inserts are additionally equipped with 2 switching contacts

## Technical Data

## EPIC® H-BVE 10



---

Rated voltage (V)	IEC: 630 V UL: 600 V CSA: 600 V
Rated impulse voltage	6 kV
Rated current (A)	IEC: 16 A UL: 16 A CSA: 16 A
Contact resistance	< 2 mOhm
Contacts	Copper alloy, hard silver-plated
Number of contacts	10 + 2 + PE
Termination methods	Screw termination: 0.5 - 2.5 mm <sup>2</sup>
Cycle of mechanical operation	100
Temperature range	-40°C to +100°C, short-term up to +125°C
VDE-tested	Certified production control: VDE-REG. no.: B437 UL-tested: UL File Number: E75770
Degree of soiling	3