



FLEXIMARK® Thermal transfer printer EOS 4 and A4+M are thermal transfer printer with a central material guidance and a print resolution of 300 dpi for high quality industrial printing.

- FLEXIMARK® EOS4 ensures excellent print quality for a fair price



## Product description

### Application range

- Printing on a variety of different materials (among others FLEXIMARK® shrink tube, cablelabel PUR and TA foam component marking)
- The thermal transfer printing method increases the smudge and scratch resistance of the printed surface, and provides increased resistance to oils and chemicals as well

### Benefits

- High print speed (up to 125 mm/sec)
- High print resolution: 300 dpi
- Easy integration into existing IT environments
- Simple communication with FLEXIMARK® marking software 10.0
- Basic maintenance such as cleaning the label sensor, changing the print head or print roller, can be easily done by yourself

## Note

- A 4+M recommended for flat shrink tube as cutter can also be used for perforations
- Other thermal transfer printing systems are available upon request

## Included

- FLEXIMARK® Thermoprint A4+M/300 or EOS4 with operation manual and service manual on CD-ROM
- Marking software  
FLEXIMARK® Software 10.0
- Windows® driver
- FLEXIMARK® Ribbon R71 55/360 resin BK (article number 83259604)
- Power supply USB cable (length 1.8 m)

## Technical Data

Dimensions	FLEXIMARK® Thermal printer A4+M: 274x242x446 mm (HxBxT) FLEXIMARK® thermoprint EOS4: 245x264x412mm (HxWxD)
Label rolls	Material thickness: 0,055-1,2 mm (A4+M), 0,055-0,7 mm (EOS4) Carrier width: 10-120 mm (A4+M), 10-116 mm (EOS4) Max. core diameter Ø: 38.0 - 100.0 mm (A4+M), 38-76 mm (EOS4)
Ribbons	Ribbon length: up to 500 m (A4+M) or 360m (EOS4)
Speed	Up to 125.00 mm/s
Weight	FLEXIMARK® Thermoprint A4+M: 9.0 kg FLEXIMARK® Thermoprint EOS4: 5 kg
Material	Labels or continuous material on coils