



FLEXIMARK® Cablelabel LFL for marking cables with cable ties (one- or two sided fastening possibility). Text can be printed on the labels with our marking software and commercial laser printers.

- LFL2H 9,9-26 contained in FLEXIMARK® sample bag (article number M3251010)



Product description

Application range

- For Cable Marking
- Printing with commercial laser printers
- Printing with FLEXIMARK® Software (Download:
<http://www.lappkabel.com/service/downloadcenter/markingsystem/markings-software.html>)

Benefits

- Can be mounted directly on the cable together with plastic cable ties
- No character holder necessary
- Printable on both sides
- Resistant to chemicals, UV-radiation, moisture and some oils
- Diverse criteria as ageing resistance and chemical resistance are tested by the independent SP Technical Research Institute of Sweden according to SP 2171 Test Method (see selection table A15)

Product Make-up

- One (LFL1H) or two-sided (LFL2H) fastening with cable ties (up to 4.5 mm in width)

Note

- Insert sheet in manual paper feed compartment
- The use of the cartridges of the printer supplier is recommended
- Optimum printing results from laser printers are achieved with straight sheet feed-in with no deflection over rollers and little heat build-up
- Dimensions refer to the marking area of the labels

Included

- A5 and A4 label sheets for laser printers

Technical Data

Colour delivered

Standard colour: Yellow/White

Material

Halogen-free polyester

Thickness: 0.175 mm

Temperature range

-40°C to +125°C