



HITRONIC® HQW-Plus armoured outdoor cable, central loose tube, corrugated steel tape, inner and outer sheath; A-DQ(ZN)B2Y(SR)2Y

- A-DQ(ZN)B2Y(SR)2Y
- Double-sheathed outdoor cable with corrugated steel tape armour, and non-metallic strength elements





Product description

Application range

- For outdoor use
- Harsh industrial environment
- Campus backbone
- WAN applications
- Methods of Deployment: empty plastic pipes, ducts and trays

Benefits

- · Additional sheath protects the fibres for use in harsh environments
- Armouring provides excellent protection against high mechanical stress and rodents
- Suitable for direct burial
- UV-resistant
 longitudinally and laterally watertight



Product Make-up

- · Gel-filled loose tube
- Water-blocking reinforced glass yarn strain relief
- Corrugated steel tape armour
- PE inner and outer sheaths
- Colour: black (RAL 9005)

Product features

- Central loose tube with up to 24 fibres
- Colour-coded fibres
- · Longitudinal watertight
- Excellent rodent protection
- Robust, halogen-free outer sheath

Technical Data

Optical fibre type

Temperature range Permissible bending radius

Permissible tensile force

Core material: glass Cladding material: glass Fixed installation: -40°C to +70°C Static: ? 15 x outer diameter Dynamic: ? 20 x outer diameter Fixed installation: 3000 N Short-term: 5000 N