# CHARGE M3 T3P/T2C S

Resistant to microbes; Resistant to oil, dust and water; Special cable design for a long service life; Flexible at low temperatures; Withstands high mechancal stress, in particular abrasion and sliding demands

- For electric vehicles with type 2 vehicle inlet

# Product description

## Application range

- For charging stations, electric and Plug-in Hybrid vehicles

## Benefits

- Resistant to microbes
- Resistant to oil, dust and water
- Special cable design for a long service life
- Flexible at low temperatures
- Withstands high mechancal stress, in particular abrasion and sliding demands

## Product Make-up

- Cable for 1-phase charging up to 20A: ÖLFLEX® Charge 3G2.5 mm²+1x0.5 mm²
- Cable for 3-phase charging up to 20A: ÖLFLEX® Charge 5G2.5mm²+1x0.5mm²
- Cable for 1-phase charging up to 32A: ÖLFLEX® Charge 3G6mm²+1x0,5mm²

- Cable for 3-phase charging up to 32 A: ÖLFLEX® Charge 5G6mm²+1x0.5mm²
- Type 2 connectors are injection moulded in two-components process for optimal ergonomics

## Technical Data

| | |
|---|---|
| Approvals | according to VDE-AR-E2283-5<br>according to EN 61851-1 |
| Temperature range | Flexing: -30°C to +50°C |


PERTRONIC CABLES SASA PERIC ROSENSTR.6 74239 HARDTHAUSEN TEL: 07139-507-8687 FAX: 07139-507-8680
www.pertronic-cables.com | sales@pertronic.eu | Skype PERTRONIC-CABLES | see you GOOGLE + PERTRONIC KABEL