



## Electron beam cross-linked cables for more demanding application requirements

For safety in areas with high density of people; Reduction of flame propagation, density and toxicity of smoke gases in event of fire; Minimises damage to buildings and equipment caused by the formation of toxic acid fumes in fires; Certified for maritime applications

- Improved characteristics in the event of a fire
- Voltage class from 1.5 mm<sup>2</sup> 450/750 V
- Please note: Discontinued product!



## Product description

### Application range

- For the wiring and connection of lighting, heating appliances, control cabinets, and distributors in mechanical and plant engineering
- For use in traffic regulation systems and outdoors

### Benefits

- For safety in areas with high density of people
- Reduction of flame propagation, density and toxicity of smoke gases in event of fire
- Minimises damage to buildings and equipment caused by the formation of toxic acid fumes in fires
- Certified for maritime applications

## Product Make-up

- Fine-wire, tinned-copper conductor
- Electron beam cross-linked polyolefin copolymer insulation
- Cores twisted in layers
- Outer sheath: electron beam cross-linked polyolefin copolymer, black

## Norm references / Approvals

- GL - Germanischer Lloyd approved

## Product features

- Low smoke density according to IEC 61034-2
- Good weather and UV-resistance
- Halogen-free according to IEC 60754-1
- Flame-retardant according IEC 60332-1-2
- No flame-propagation according to IEC 60332-3-24 respectively IEC 60332-3-25 (Flame spread on vertical cable or wire bundle)

## Technical Data

Core identification code	Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 7 cores: black with white numbers
Classification	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Conductor stranding	Fine wire acc. to VDE 0295, class 5 / IEC 60228 class 5 from 0.5 mm <sup>2</sup>
Minimum bending radius	Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage	Up to 1.0mm <sup>2</sup> U <sub>0</sub> /U 300/500 V From 1.5mm <sup>2</sup> U <sub>0</sub> /U 450/750 V 0.6/1kV from 1.5 mm <sup>2</sup> in the case of fixed and protected installation
Test voltage	3500 V
Protective conductor	G = with GN-YE protective conductor X = without protective conductor
Temperature range	Occasional flexing: -35 °C to +120 °C Fixed installation: -55 °C to +125 °C Short-term: up to +145 °C