



## Abrasion-resistant PUR control cables, flexible at cold temperatures – halogen-free and flame-retardant

Increased durability under harsh conditions thanks to robust PUR outer sheath; Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media; Wide temperature range for applications in harsh climatic environments; VDE-tested characteristics

- Suitable for all weather conditions
- Flexible at low temperatures
- VDE-tested and registered



## Product description

### Application range

- Industrial machinery and machine tools
- Very suitable for oily wet areas within machinery and production lines that are subject to normal mechanical stress
- Construction machinery
- Agricultural equipment
- For indoor and outdoor use

### Benefits

- Increased durability under harsh conditions thanks to robust PUR outer sheath
- Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and

other chemical media

- Wide temperature range for applications in harsh climatic environments
- VDE-tested characteristics

## Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation: TPE
- Cores twisted in layers
- Special polyurethane outer sheath (PUR)
- Sheath colour: silver grey (RAL 7001)

## Norm references / Approvals

- VDE reg. no. 6582

## Product features

- Resistant to oil and drilling fluids according to IEC 61892-4, Appendix D
- Abrasion and notch-resistant
- Halogen-free and flame-retardant (IEC 60332-1-2)
- Resistant to hydrolysis and microbes
- Flexible down to -40°C

## Technical Data

Core identification code	Black with white numbers acc. to VDE 0293-1
Classification	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Conductor stranding	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius	Occasional flexing: 12.5 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage	U <sub>0</sub> /U: 300/500 V
Test voltage	3000 V
Protective conductor	G = with GN-YE protective conductor X = without protective conductor
Temperature range	Occasional flexing: -40°C to +90°C Fixed installation: -50°C to +90°C