



Screened and abrasion-resistant control cables with PUR sheath for increased application requirements

Increased durability under harsh conditions thanks to robust PUR outer sheath; Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media; Copper braiding screens the cable against electromagnetic interference

- High mechanical strength
- Good oil resistance
- EMC compliant copper screening



Product description

Application range

- Machine tools
- Industrial machinery and machine tools
- Measurement, control and electrical applications
- Very suitable for oily wet areas within machinery and production lines that are subject to normal mechanical stress
- Outdoor use is possible within the indicated operating temperature range

Benefits

- Increased durability under harsh conditions thanks to robust PUR outer sheath

- Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media
- Copper braiding screens the cable against electromagnetic interference

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: special PVC
- Cores twisted in layers
- PVC inner sheath, grey
- Tinned-copper braiding
- Special polyurethane outer sheath (PUR)
- Sheath colour: silver grey (RAL 7001)

Norm references / Approvals

- Based on VDE 0285

Product features

- High oil-resistance
- Abrasion and notch-resistant
- EMC-compliant
- Low-adhesive surface
- Resistant to hydrolysis and microbes

Technical Data

Core identification code	Black with white numbers acc. to VDE 0293-1
Classification	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Conductor stranding	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius	Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter
Nominal voltage	U ₀ /U: 300/500 V
Test voltage	4000 V
Protective conductor	G = with GN-YE protective conductor X = without protective conductor
Temperature range	Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C