



## Flexible single-conductor rubber cable with 1.8/3 kV rated voltage

Arrangements made of single-conductor cables NSGAFÖU in accordance with VDE 0250 Part 602 with nominal voltage of at least  $U_0/U$ : 1.8/3 kV can be used for short circuit-proof and short-to-ground-proof installation up to 1000 V in acc. with VDE 0100 Part 520 and VDE 0298 Part 3

- Public transport
- Control panel internal wiring



## Product description

### Application range

- Wiring of machines, tools, devices, appliances and control cabinets
- Railway vehicles, buses, switching stations (short-circuit-proof up to 1000 V), power distributors (short-circuit-proof up to 1000 V)
- No direct burial, except of lead-through through fire separations such as sand cups
- In ducts, tubes, pipes, conduits and closed installation channels
- Bundled or for connection of movable parts

### Benefits

- Arrangements made of single-conductor cables NSGAFÖU in accordance with VDE 0250 Part 602 with nominal voltage of at least  $U_0/U$ : 1.8/3 kV can be used for short circuit-proof and short-to-ground-proof installation up to 1000 V in acc. with VDE 0100 Part 520 and VDE 0298 Part 3

## Product Make-up

- Fine-wire strand made of tinned-copper wires
- Core insulation: rubber compound type 3GI3
- Outer coating: rubber compound, type 5GM3
- No outer sheath

## Norm references / Approvals

- certification according to the VDE cable type NSGAFÖU 1,8/3 kV acc. VDE 0250-602

## Product features

- Flame-retardant according IEC 60332-1-2
- Oil-resistant according to EN 60811-404
- Normative rated voltage classes  $U_0/U$  0.6/1 kVac and 3.6/6 kVac available on request

## Technical Data

Classification	ETIM 5.0 Class-ID: EC000993
Conductor stranding	ETIM 5.0 Class-Description: Single core cable Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius	Flexible use: 10 x outer diameter Fixed installation: 6 x outer diameter
Nominal voltage	$U_0/U$ : 1.8/3 kV
Test voltage	6000 V
Current rating	According to VDE 0298 Part 4, Table 15
Temperature range	Flexible use: -25°C to +90°C Fixed installation: -40°C to +90°C