



Screened, TPE-insulated, numbered, TPE inner and special polymer outer sheath

Suitable for long horizontal drag chain travel distances; Reduced outer diameters enable space and weight saving installation; Suitable for contact with oil- and ester-based drilling muds as well as calcium bromide solutions usually used on drilling rigs; Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media; Copper braiding screens the cable against electromagnetic interference

- Resistant to oil and drilling fluids acc. to NEK TS 606:2009 (Oil & Mud)
- Extended Line for heavy duty in power chain applications



Product description

Application range

- Permanently moved power chains or machine parts in harsh environment
- Onshore and offshore applications
- In wet areas within machinery and production or assembly lines

Benefits

- Suitable for long horizontal drag chain travel distances
- Reduced outer diameters enable space and weight saving installation
- Suitable for contact with oil- and ester-based drilling muds as well as calcium bromide solutions usually used on drilling rigs

- Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media
- Copper braiding screens the cable against electromagnetic interference

Product Make-up

- Extra-fine wire strand made of bare copper
- Core insulation: TPE
- Cores twisted in short lay lengths
- Non-woven wrapping
- Inner sheath made of TPE
- Tinned copper screen braiding
- Outer sheath made of robust special polymer, colour black

Norm references / Approvals

- Based on VDE 0250 / 0285
- Resistant against oil and drilling fluids according to NEK TS 606:2009 and IEC 61892-4
- Salt water-resistant according to UL 1309
- For use in power chains: Please comply with the assembly guidelines listed in Appendix T3

Product features

- Good notch and abrasion resistance
- Good weather, ozone, UV and oil resistance
- Halogen-free and flame-retardant (IEC 60332-1-2)
- Resistant to hydrolysis and microbes
- Designed for 10 million alternating bending cycles and horizontal travel distances up to 100 meter

Technical Data

Core identification code	Black with white numbers acc. to VDE 0293-1
Classification	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Conductor stranding	Extra-fine wire acc. to VDE 0295, class 6/ IEC 60228 class 6
Minimum bending radius	For flexible use: 7.5 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage	U ₀ /U: 300/500 V
Test voltage	3000 V
Protective conductor	G = with GN-YE protective conductor X = without protective conductor
Temperature range	Flexing: -50°C to +80°C Fixed installation: -60°C to +90°C