



Colour-coded PVC control cable with steel wire braiding

Extra mechanical protection due to braided steel wire

- Steel wire braiding for extra mechanical protection



Product description

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
- Areas with high mechanical stress

Benefits

- Extra mechanical protection due to braided steel wire

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- PVC inner sheath, grey

- Braid of galvanized steel wires
- PVC outer sheath, transparent

Norm references / Approvals

- Based on IEC 60227-5 and EN 50525-2-51

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1

Technical Data

Core identification code	Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: ÖLFLEX® colour code, refer to Appendix T7
Classification	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Conductor stranding	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius	Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter
Nominal voltage	Up to 1.5 mm ² : U ₀ /U: 300/500 V From 2.5 mm ² : U ₀ /U: 450/750 V From 2.5 mm ² , in the case of fixed and protected installations: U ₀ /U: 600/1000 V
Test voltage	4000 V
Protective conductor	G = with GN-YE protective conductor X = without protective conductor
Temperature range	Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C