



## H05VV5-F (EN 50525-2-51)

High acceptance in Europe due to Harmonisation

- Oil-resistant according to EN 50363-4-1: TM5
- Harmonised (HAR): H05VV5-F



## Product description

### Application range

- Plant engineering  
Industrial machinery  
Heating and air-conditioning systems
- Machine tools
- Mainly used in dry, damp and wet interiors (including water-oil mixtures), but not for outdoor use
- For fixed installation under medium mechanical load conditions, and applications with occasional flexing at free, non-continuously recurring movement without tensile load or compulsory guidance

### Benefits

- High acceptance in Europe due to Harmonisation

### Product Make-up

- Fine-wire strand made of bare copper wires
- PVC core insulation
- PVC outer sheath, high oil-resistance, grey (RAL 7001)

## Norm references / Approvals

- EN 50525-2-51

## Product features

- Flame-retardant according IEC 60332-1-2
- Oil-resistant according to EN 50363-4-1: TM5

## Technical Data

Core identification code	Black with white numbers acc. to VDE 0293-1
Classification	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Conductor stranding	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius	Occasional flexing: 12.5 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage	U <sub>0</sub> /U: 300/500 V
Test voltage	3000 V
Protective conductor	G = with GN-YE protective conductor X = without protective conductor
Temperature range	Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +70°C