



Optimum cable and conduit strain relief; Maximum cable sealing; Fast and easy assembly; Wide clamping range; Anti-turn protection



Product description

Application range

- In combination with protective conduit:
- SILVYN® AS
- SILVYN® EDU-AS/EMC AS-CU/AS-P
- Indoor / outdoor applications
- Used in areas where cables and wires need to be provided with strain relief and additional sealing

Benefits

- Optimum cable and conduit strain relief
- Maximum cable sealing
- Fast and easy assembly
- Wide clamping range
- Anti-turn protection

Product Make-up

- Optional:
- SKINTOP® MS-M cable gland
- SKINTOP® MS-SC-M EMC connection
- SKINTOP® DIX multiple sealing insert
- SILVYN® conduit connection via inner sleeve and cap nut

Note

- For suitable accessories, refer to SKINTOP® metric accessories

Product features

- Combination of SILVYN® and SKINTOP®

Technical Data

Material

Basis type:

Body: nickel-plated brass

Conduit connector seal: CR/NBR

Tube seal: TPE

Protection rating

Cable: IP 68

Conduit:

IP 40 with SILVYN® AS, EDU-AS, EMC AS-CU

IP 54 with SILVYN® FPS, FPS-EDU, FD-PU, AS-P

Temperature range

-30°C to +100°C