



Conical NPT thread; Maximum reliability; Optimum strain relief; Wide, variable clamping ranges



Product description

Application range

- In areas where mechanical and chemical stability are critical
- Chemical industry
- Measurement and control technology
- Machine and equipment manufacturing
- Plant engineering

Benefits

- Conical NPT thread
- Maximum reliability
- Optimum strain relief
- Wide, variable clamping ranges

Product Make-up

- NPT connection thread acc. to ANSI B1.20.2 - 1983

Product Make-up

- SKINTOP® MSR NPT is equipped with a reduction seal insert to seal cables and wires with small outer diameters

Norm references / Approvals

- UL File Nr. E79903

Note

- Refer to SKINTOP® metric accessories for suitable accessories. Note that SKINDICHT® SM-M counter nut is not compatible with this model.
- 1/4" = M12, 3/8" = M16
- 1/2" = M20, 3/4" = M25
- 1" = M32, 1 1/4" = M40
- 1 1/2" = M50, 2" = M63

Technical Data

Classification

ETIM 5.0 Class-ID: EC000441

Material

ETIM 5.0 Class-Description: cable screw gland

Body: nickel-plated brass

Insert: polyamide

Sealing ring: CR

O-ring: NBR

Protection rating

IP 68 - 10 bar

Temperature range

-30°C to +100°C