



Perfect seal with anti-kink protection; Optimum, low-resistance 360° screen contact; Cable-protecting strain relief; Gentle cable clamping; High degree of protection



Product description

Application range

- Earthing gland with additional anti-kink protection. For applications where electrical interference fields can occur.
- Moving machine parts
- Conveyor and transport systems
- Production lines
- Measurement and control technology

Benefits

- Perfect seal with anti-kink protection
- Optimum, low-resistance 360° screen contact
- Cable-protecting strain relief
- Gentle cable clamping
- High degree of protection

Product Make-up

- Metric connection thread acc. to EN 50262

Note

- Counter nut to be used: SKINDICHT® SM-M
- SKINDICHT® SM-PE-M counter nut should be used to ensure optimum contact with painted, anodised or powder-coated housings
- Example description:
SRE-M 20/13.5/9/6
20 = connection thread
13.5 = PG function thread
9 = clear opening of anti-kink sleeve
6 = clear opening of earthing sleeve

Technical Data

Caution	The installation dimensions can be found in appendix T21
On request	Available with long connection thread
Classification	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Material	Body: nickel-plated brass Earthing sleeve: plain brass Anti-kink sleeve: CR/NBR O-ring: NBR
Protection rating	IP 65
Temperature range	-20°C to +80°C