



Cold impact resistance; High strain relief; Wide, variable clamping ranges; Anti-static; Maximum reliability



## Product description

### Application range

- Devices, machines and apparatus of enhanced safety protection type "e"
- Equipment group II / Category 2G+1D
- For mobile applications in offshore and marine industries
- Chemical and petrochemical industry

### Benefits

- Cold impact resistance
- High strain relief
- Wide, variable clamping ranges
- Anti-static
- Maximum reliability

### Product Make-up

- Metric connection thread acc. to EN 50262

## Norm references / Approvals

- UL File Nr. E79903

## Note

- Refer to SKINTOP® SDV-M ATEX for suitable accessories

## Product features

- SKINTOP® MS-M-XL ATEX is similar to the SKINTOP® MS-M ATEX, but has an extended connection thread for thick walls

## Technical Data

Caution	Refer to the instruction leaflet for the installation dimensions and torques
Approvals	CE 0637 Ex II 2G Ex eb IIC Ex II 1D Ex ta IIIC IECEX IBE 13.0026X
Classification	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Material	Body: nickel-plated brass Insert: polyamide Sealing ring: CR O-ring: NBR
Tests	DIN EN 60079-0 DIN EN 60079-7
Protection rating	IP 68 - 10 bar
Temperature range	-30°C to +90°C