




High mechanical stability; Long service life; Optimum strain relief; Wide, variable clamping ranges; Maximum reliability

- Permanent bending protection under high mechanical stress



Product description

Application range

- In areas where mechanical stability are critical
- Portable equipment
- Building sites
- Machine and equipment manufacturing
- Typical fields of application
 - Steel and glass works
 - Cement and ceramic works
 - Foundries
 - Shipbuilding industry
 - Furnace construction

Benefits

- High mechanical stability
- Long service life
- Optimum strain relief

- Wide, variable clamping ranges
- Maximum reliability

Product Make-up

- Metric connection thread acc. to EN 50262

Norm references / Approvals

- Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Note

- Counter nut to be used: SKINDICHT® SM-M
- Refer to SKINTOP® metric accessories for suitable accessories

Technical Data

Caution	Refer to Appendix T21 for the installation dimensions and torques
Classification	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Material	Body: nickel-plated brass Insert: polyamide Sealing ring: CR O-ring: NBR Spiral - springs made of stainless steel
Protection rating	IP 68 - 10 bar IP 69 K
Temperature range	Dynamic: -30 °C to +100 °C