



Maximum reliability; Optimum strain relief; Wide, variable clamping ranges; For cable diameters up to 98 mm

- SKINTOP® MS-M sizes 75 x 1.5 to 110 x 2 with innovative double lamella gasket for easier assembling of cables with large diameters.
- Now with IP 69 K approval! Proven to withstand the most demanding cleaning procedures for industrial machinery with high-pressure cleaners and hot water!



Product description

Application range

- In areas where mechanical and chemical stability are critical
- Chemical industry
- Measurement and control technology
- Machine and equipment manufacturing
- Plant engineering

Benefits

- Maximum reliability
- Optimum strain relief
- Wide, variable clamping ranges
- For cable diameters up to 98 mm

Product Make-up

- Metric connection thread acc. to EN 50262

Norm references / Approvals

- UL File Nr. E79903

Note

- Counter nut to be used: SKINDICHT® SM-M
- Refer to SKINTOP® metric accessories for suitable accessories

Technical Data

Caution	Refer to Appendix T21 for the installation dimensions and torques
Approvals	IP 69 K approval from size M75 x 1.5 pending. UL, CSA, DNV and VDE approval for sizes M90 x 2 to M110 x 2 pending.
Classification	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Note	In stainless steel V2A available
Material	Body: nickel-plated brass Insert: polyamide Sealing ring: CR O-ring: NBR
Protection rating	IP 68 - 10 bar (M12 - M50) IP 68 - 5 bar (M63) IP 69 K (M12 - M63)
Temperature range	Dynamic: -30 °C to +100 °C Fixed: -40°C to +100°C