



For the benefits, refer to SKINTOP® MS-M

- SKINTOP® MSR-M 75 x 1.5 with innovative double lamella gasket for easier assembling of cables with large diameters.
- Now with IP 69 K approval! Proven to withstand the most demanding cleaning procedures for industrial machinery with high-pressure cleaners and hot water!























# **Product description**

### **Application range**

• With reducing seal insert, to seal cables with smaller outer diameters.

#### **Benefits**

• For the benefits, refer to SKINTOP® MS-M

## **Product Make-up**

• Metric connection thread acc. to EN 50262

### Norm references / Approvals

#### **SKINTOP® MSR-M**



• UL File Nr. E79903

#### **Note**

- Counter nut to be used: SKINDICHT® SM-M
- Refer to SKINTOP® metric accessories for suitable accessories

### **Technical Data**

Caution Refer to Appendix T21 for the installation dimensions and

torques

Approvals IP 69 K approval from size M75 x 1.5 pending.

UL, CSA, DNV and VDE approval for sizes M90 x 2 to

M110 x 2 pending.

Classification ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: cable screw gland

Note In stainless steel V2A available

Material Body: nickel-plated brass Insert: polyamide

Sealing ring: CR O-ring: NBR

Protection rating IP 68 - 1 bar (M63 plus - M75)

IP 69 K (M12 - M63)

Temperature range Dynamic: -30 °C to +100 °C

Fixed: -40°C to +100°C