



Reliable bending and anti-kink protection; Cable conservation; Functional reliability; To protect flexible cables



Product description

Application range

- Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1
- Handheld device
- Robotics industry
- Light and sound applications
- Moving machine parts

Benefits

- Reliable bending and anti-kink protection
- Cable conservation
- Functional reliability
- To protect flexible cables

Product Make-up

- Metric connection thread acc. to EN 50262

Norm references / Approvals

- UL File Nr. E79903

Note

- Refer to SKINTOP® metric accessories for suitable accessories
- Counter nut to be used: SKINTOP® GMP-GL-M
- Version with reducing insert to seal smaller cable cross-sections SKINTOP® BSR-M on request
- SKINTOP® BS M ISO versions with extra-long connection thread, see table, no DNV approval

Technical Data

Caution	Refer to Appendix T21 for the installation dimensions and torques
On request	with reducing sealing ring
Classification	ETIM 5.0 Class-ID: EC000441
	ETIM 5.0 Class-Description: cable screw gland
Colour delivered	Silver grey (RAL 7001) Light grey (RAL 7035) Black (RAL 9005), UV-resistant
Material	Body: Polyamide Seal: CR
Protection rating	IP 68 - 5 bar IP 69 K pending
Temperature range	-20°C to +100°C