



Reliable bending protection for cable conservation and functional reliability; Save up to 70% of the time with the innovative CLICK system; No thread required; To protect flexible cables; Fewer parts, counter nut no longer needed

- The most innovative cable insertion system in the market for a fast and highly flexible assembly. Simply click in - turn to the left - turn to the right - finished. The result: fixed, centred, strain-relieved fitting and maximum protection class in a few seconds.



Product description

Application range

- Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1
- Robotics industry
- Moving machine parts
- Apparatus construction
- Light and sound applications

Benefits

- Reliable bending protection for cable conservation and functional reliability
- Save up to 70% of the time with the innovative CLICK system
- No thread required
- To protect flexible cables

- Fewer parts, counter nut no longer needed

Norm references / Approvals

- UL File Nr. E79903

Included

- Included: disassembly tool

Technical Data

Classification	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Colour delivered	Silver grey (RAL 7001) Light grey (RAL 7035) Black (RAL 9005), UV-resistant
Material	Body: special polyamide Seal: special elastomer
Protection rating	IP 68 - 4 bar (M12) IP 68 - 5 bar (M16 - M32)
Temperature range	-20°C to +100°C