



## SKINTOP® for photovoltaics

UV and ozone-resistant; UL 746 C - UL F1 outdoor use; High strain relief; Permanent vibration protection; Extremely flame-retardant according to UL 94V-0 / 94-5VA

- Cable gland for photovoltaik applications, based on EN 50262, EN 50548 and UL 1703.
- Extended temperature range



## Product description

### Application range

- Photovoltaic plants and solar parks

### Benefits

- UV and ozone-resistant
- UL 746 C - UL F1 outdoor use
- High strain relief
- Permanent vibration protection
- Extremely flame-retardant according to UL 94V-0 / 94-5VA

### Product Make-up

- Metric connection thread acc. to EN 50262

## Norm references / Approvals

- UL File Nr. E79903

## Note

- Counter nut to be used: SKINDICHT® SM-M
- Counter nut to be used: SKINTOP® GMP-GL-M

## Technical Data

Caution	Refer to Appendix T21 for the installation dimensions and torques
Classification	ETIM 5.0 Class-ID: EC000441
Colour delivered	ETIM 5.0 Class-Description: cable screw gland
Material	RAL 9005 black/UV-resistant
Tests	Body: Polycarbonate
Protection rating	Seal: CR
Temperature range	Cold impact test according to UL 1703/UL 746 C
	IP 68 - 5 bar
	-40°C to +100°C