



SKINTOP® halogen-free

Maximum reliability; Extremely flame-retardant according to UL 94 V0; Completely halogen-free (including sealing material); Self-extinguishing, no dripping; Permanent vibration protection

- Cable gland for railway applications- Fire protection on railway vehicles Approval according to DIN EN 45545-2:2013



Product description

Application range

- When the protection of people and property is a priority.
- Public buildings
- Ventilation systems
- Tunnel construction
- Underground railways and trains

Benefits

- Maximum reliability
- Extremely flame-retardant according to UL 94 V0
- Completely halogen-free (including sealing material)
- Self-extinguishing, no dripping
- Permanent vibration protection

Product Make-up

- Metric connection thread acc. to EN 50262

Technical Data

Caution	Refer to Appendix T21 for the installation dimensions and torques
Classification	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Colour delivered	Light grey (RAL 7035)
Material	Polyamide UL 94V-0 - halogen-free Sealing ring: LSE 1 - halogen-free O-ring: LSE 1 - halogen-free
Tests	Filament wire test EN 60695-2-1/1 +960°C
Protection rating	IP 68 - 5 bar
Temperature range	-20°C to +100°C