




Suitable for cables with and without inner sheath; Also suitable for continuing the cable screen to another connection; Low-resistance screen contact, optimum EMC protection; Highly conductive, flexible EMC contact for clamping various screen diameters; Few operation steps, easy to assemble



Product description

Application range

- For EMC-compliant earthing of the copper braiding, or for cables with copper shaft sheath
- Automation technology
- Telecommunication
- Measurement and control technology
- Industrial machinery and plant engineering

Benefits

- Suitable for cables with and without inner sheath
- Also suitable for continuing the cable screen to another connection
- Low-resistance screen contact, optimum EMC protection
- Highly conductive, flexible EMC contact for clamping various screen diameters
- Few operation steps, easy to assemble

Product Make-up

- PG connection thread

Note

- Refer to SKINTOP® PG accessories for suitable accessories
- EMC counter nut, SKINDICHT® SM nut should be used to ensure optimum contact with painted, anodised or powder-coated housings

Technical Data

Caution	Refer to Appendix T21 for the installation dimensions and torques
Classification	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Material	Body: nickel-plated brass Insert: polyamide Sealing ring: CR O-ring: NBR
Protection rating	IP 68 - 10 bar
Temperature range	-30°C to +100°C