



Description: A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 30_

Lapp code: Lapp 1591155

The **Test voltage** of the cable Lapp 1591155 is Core/core: 500 V Core/screen: 2000 V.

Application range

- External cables for telecommunication and data processing systems
- Do not install cables that are meant to be placed in ducts or for direct burial in areas exposed to fire hazards

Product Make-up

- Solid bare copper conductor
- Core insulation made of polyethylene (PE)
- 5 star-quads are twisted into each basic unit, which is then twisted together with the main unit to form the cable core
- Paper tape wrapping
- Laminated sheath with aluminium-coated plastic tape, PE outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 1591155 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of double cores | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---|--------------|------------------------|---------------------|----------------------|----------------|
| A-2Y(L)2Y...STIII BD copper conductor 0.6 mm | | | | | |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 2 | Lapp 1591050 | 2 | 8.1 | 11.0 | 65 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 4 | Lapp 1591051 | 4 | 10.0 | 23.0 | 90 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 6 | Lapp 1591052 | 6 | 10.3 | 34.0 | 110 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 10 | Lapp 1591053 | 10 | 11.5 | 57.0 | 140 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 20 | Lapp 1591054 | 20 | 15.5 | 113.0 | 230 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 30 | Lapp 1591055 | 30 | 16.6 | 170.0 | 320 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 40 | Lapp 1591056 | 40 | 18.0 | 226.0 | 400 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 50 | Lapp 1591057 | 50 | 19.5 | 283.0 | 470 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 70 | Lapp 1591058 | 70 | 23.0 | 396.0 | 610 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 200 | Lapp 1591061 | 200 | 36.5 | 1131.0 | 1600 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 300 | Lapp 1591063 | 300 | 44.0 | 1696.0 | 2300 |
| A-2Y(L)2Y...ST III BD copper conductor 0.8 mm | | | | | |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 2 | Lapp 1591150 | 2 | 8.6 | 20.0 | 75 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 4 | Lapp 1591151 | 4 | 10.9 | 40.0 | 120 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 6 | Lapp 1591152 | 6 | 11.5 | 60.0 | 145 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 10 | Lapp 1591153 | 10 | 13.5 | 101.0 | 200 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 14 | Lapp 1591163 | 14 | 16.5 | 141.0 | 270 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 20 | Lapp 1591154 | 20 | 17.3 | 201.0 | 340 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 30 | Lapp 1591155 | 30 | 19.0 | 302.0 | 480 |

A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 30_

Lapp 1591155



| Product Name | Lapp Nr. | Number of double cores | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--|--------------|------------------------|---------------------|----------------------|----------------|
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 40 | Lapp 1591156 | 40 | 20.7 | 402.0 | 610 |
| A-2Y(L)2Y...ST III BD Telephone Outdoor Cable 50 | Lapp 1591157 | 50 | 23.7 | 503.0 | 750 |