



Description: Coaxial cables RGB_

Lapp code: Lapp 0034245

The **Test voltage** of the cable Lapp 0034245 is /.

Application range

- Colour monitor cable for PCs and CAD workstations, process visualisation
- For fixed installation in rooms (RGB CY..x Kx 0.4/1.8)
- For highly flexible applications in power chains (energy supply chains) and continuously moving machine components (RGB-FD..x Kx 0.6L/2.4)

Product Make-up

- Conductor: tinned-copper wire
- Dielectric: cellular polyolefin
- Outer conductor: copper braiding or tinned-copper wire wrapping
- Red (R), green (G), blue (B) elements - for RGB 5 x Kx 0.4/1.8 red, green, blue, white, black
- PVC outer sheath
FD Version with PUR outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 0034245 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Fixed installation					
Coaxial cables RGB	Lapp 0034245	RGB CY 3 x Kx 0,4/1,8 + 3 x 0,25	8,0	51,0	97
Coaxial cables RGB	Lapp 0034246	RGB DY 5 x Kx 0,4/1,8	9,7	60,0	132
Flexible and highly flexible applications					
Coaxial cables RGB	Lapp 0034247	RGB-FD 3 x Kx 0,6L/2,4	10,8	29,0	100