



**Description:** Conductor end sleeves XL, insulated\_

**Lapp code:** Lapp 61802065

The **Test voltage** of the cable Lapp 61802065 is /.

## Application range

- Suitable conductor end sleeves for UL(MTW)-CSA-HAR multi-standard single cores

## Product Make-up

- Because of their approval for numerous markets, special conductor end sleeves with the cross sections listed below are needed for our multi-standard single cores.
- The conductor is permanently connected to the collar by crimping

In our Cable list on next page you can find all interesting information acc. article Lapp 61802065 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	For mm <sup>2</sup>	AWG	Colour	l1 mm	l2 mm	d 1 mm	s1 mm	d 2 mm	s2 mm	Pieces / PU
Conductor end sleeves XL, insulated	Lapp 61802061	Conductor end sleeves XL 0.5 WH 8	0,5	20	white	13.5	8	1.1	0.15	3.00	0.25	500
Conductor end sleeves XL, insulated	Lapp 61802062	Conductor end sleeves XL 0.5 WH 10	0,5	20	white	15.5	10	1.1	0.15	3.00	0.25	500
Conductor end sleeves XL, insulated	Lapp 61802063	Conductor end sleeves XL 0.75 GY 8	0,75	18	grey	14.00	8	1.3	0.15	3.4	0.3	500
Conductor end sleeves XL, insulated	Lapp 61802064	Conductor end sleeves XL 0.75 GY 10	0,75	18	grey	16.00	10	1.3	0.15	3.4	0.3	500
Conductor end sleeves XL, insulated	Lapp 61802065	Conductor end sleeves XL 1.0 RD 8	1.00	18	red	14.00	8	1.5	0.15	3.4	0.3	500
Conductor end sleeves XL, insulated	Lapp 61802066	Conductor end sleeves XL 1.0 RD 10	1.00	18	red	16.00	10	1.5	0.15	3.4	0.3	500
Conductor end sleeves XL, insulated	Lapp 61802067	Conductor end sleeves XL 1.5 BK 8	1,5	16	black	14.00	8	1.8	0.15	3.8	0.3	500
Conductor end sleeves XL, insulated	Lapp 61802068	Conductor end sleeves XL 1.5 BK 10	1,5	16	black	16.00	10	1.8	0.15	3.8	0.3	500
Conductor end sleeves XL, insulated	Lapp 61802069	Conductor end sleeves XL 16.0 BU 12	16.00	6	blue	23.00	12	6.00	0.2	9.5	0.4	100