



Description: EPIC SOLAR 4 THIN F pre-assembled_
Lapp code: Lapp 44428104

The **Test voltage** of the cable Lapp 44428104 is /.

Application range

- Pre-assembled connection cables for weatherproof cabling of photovoltaic systems

/

In our Cable list on next page you can find all interesting information acc. article Lapp 44428104 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Cross-section (mm ²)	Rated current (A)	Length (m)	Copper index (kg/km)	Pieces / PU
EPIC® SOLAR 4 THIN female with cable ÖLFLEX® SOLAR XLR							
EPIC SOLAR 4 THIN F pre-assembled	Lapp 44428104	EPIC® SOLAR 4 THIN F XLR TF 1.5 mm ² 1 m	1,5	17	1	14.4	100
EPIC SOLAR 4 THIN F pre-assembled	Lapp 44428105	EPIC® SOLAR 4 THIN F XLR TF 2.5 mm ² 1 m	2,5	21	1	24.0	100
EPIC SOLAR 4 THIN F pre-assembled	Lapp 44428106	EPIC® SOLAR 4 THIN F XLR TF 4mm ² 1m	4	25	1	38.4	100
EPIC SOLAR 4 THIN F pre-assembled	Lapp 44428107	EPIC® SOLAR 4 THIN F XLR 6mm ² 1m	6	30	1	57.6	100
EPIC® SOLAR 4 THIN female with cable ÖLFLEX® SOLAR XL multi							
EPIC SOLAR 4 THIN F pre-assembled	Lapp 44428111	EPIC® SOLAR 4 THIN F XL multi 2.5 mm ² 1 m	2,5	21	1	24.0	100
EPIC SOLAR 4 THIN F pre-assembled	Lapp 44428112	EPIC® SOLAR 4 THIN F XL multi 4mm ² 1m	4	25	1	38.4	100
EPIC SOLAR 4 THIN F pre-assembled	Lapp 44428113	EPIC® SOLAR 4 THIN F XL multi 6mm ² 1m	6	30	1	57.6	100