



Description: ESUY Copper Earthing Cable 25_

Lapp code: Lapp 4571102

The **Test voltage** of the cable Lapp 4571102 is 2000 V.

Application range

- Provides protection during repairs
- For earthing in high-voltage power installations of power companies and railway systems
- For earthing devices and potential equalisation on machine parts and EDP systems

Product Make-up

- Strands of bare copper wires
- Braiding made of bare copper wires
- PVC-based outer sheath, transparent

In our Cable list on next page you can find all interesting information acc. article Lapp 4571102 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm ²)	Conductor stranding: number of wires x wire diameter (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ESUY Copper Earthing Cable 16	Lapp 4571101	16	4200 x 0,07	8,8	177.0	230
ESUY Copper Earthing Cable 25	Lapp 4571102	25	3192 x 0,1	10,4	275.0	316
ESUY Copper Earthing Cable 35	Lapp 4571103	35	4480 x 0,1	12,4	387.0	475
ESUY Copper Earthing Cable 50	Lapp 4571104	50	6383 x 0,1	14,6	560.0	670
ESUY Copper Earthing Cable 70	Lapp 4571105	70	8918 x 0,1	17.0	791.0	905
ESUY Copper Earthing Cable 95	Lapp 4571106	95	12100 x 0,1	19,8	1069.0	1220