



**Description:** ESUY Copper Earthing Cable 70\_

**Lapp code:** Lapp 4571105

The **Test voltage** of the cable Lapp 4571105 is 2000 V.

## Application range

- Provides protection during repairs
- For earthing in high-voltage power installations of power companies and railway systems
- For earthing devices and potential equalisation on machine parts and EDP systems

## Product Make-up

- Strands of bare copper wires
- Braiding made of bare copper wires
- PVC-based outer sheath, transparent

In our Cable list on next page you can find all interesting information acc. article Lapp 4571105 and much more.

CABLE LIST - all informations you need you can find here

| Product Name                  | Lapp Nr.     | Conductor cross-section (mm <sup>2</sup> ) | Conductor stranding: number of wires x wire diameter (mm) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------------|--------------|--|---|---------------------|----------------------|----------------|
| ESUY Copper Earthing Cable 16 | Lapp 4571101 | 16   | 4200 x 0,07   | 8,8                 | 177.0                | 230            |
| ESUY Copper Earthing Cable 25 | Lapp 4571102 | 25   | 3192 x 0,1  | 10,4                | 275.0                | 316            |
| ESUY Copper Earthing Cable 35 | Lapp 4571103 | 35   | 4480 x 0,1  | 12,4                | 387.0                | 475            |
| ESUY Copper Earthing Cable 50 | Lapp 4571104 | 50   | 6383 x 0,1  | 14,6                | 560.0                | 670            |
| ESUY Copper Earthing Cable 70 | Lapp 4571105 | 70   | 8918 x 0,1  | 17.0                | 791.0                | 905            |
| ESUY Copper Earthing Cable 95 | Lapp 4571106 | 95   | 12100 x 0,1   | 19,8                | 1069.0               | 1220           |