



Description: ETHERLINE Cat.5 ARM_
Lapp code: Lapp 2170496

The **Test voltage** of the cable Lapp 2170496 is Core/core: 2000 V Core/screen: 2000 V.

Application range

- Can be used for Industrial Ethernet in harsh industrial environments
- 2pair: 10/100 Mbit/s for Industrial Ethernet
- Suitable for outdoor use, UV-resistant
- PROFINET application Type C but for fixed installation
- Suitable for direct burial

Product Make-up

- Solid and bare copper conductor
- Core insulation: PE
- Overlapping plastic tape
- SF/UTP: copper braid and foil screening as overall screening
- Inner sheath made of PVC (green RAL6018)
2 layer galvanizid steel tape
- Outer sheath made of black polyethylene (PE)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170496 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Fixed installation						
ETHERLINE Cat.5 ARM	Lapp 2170496	ETHERLINE® Cat.5 ARM	2 x 2 x AWG22/1	6,7 / 9,8	30.4	124