



Description: ETHERLINE Cat.6A + Cat.7_

Lapp code: Lapp 2170474

The **Test voltage** of the cable Lapp 2170474 is /.

Application range

- for industrial secondary and tertiary cabling according to EN 50173-3 ISO/IEC 24702
- Fixed installation
- Can be used in dry or damp rooms
- For PROFINET applications type A

Product Make-up

- Solid bare copper wire AWG22
- Core insulation made of polyethylene (PE)
- S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
- Colour: green (based on RAL 6018)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170474 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Outer sheath: halogen-free, flame-retardant compound						
ETHERLINE Cat.6A + Cat.7	Lapp 2170466	ETHERLINE® Cat.6A H	4 x 2 x AWG22/1	9.0	53.0	99
ETHERLINE Cat.6A + Cat.7	Lapp 2170476	ETHERLINE® CAT.7 H	4 x 2 x AWG22/1	9.0	53.0	99
Outer sheath: PUR, halogen-free						
ETHERLINE Cat.6A + Cat.7	Lapp 2170465	ETHERLINE® CAT.6A P	4 x 2 x AWG22/1	9.0	53.0	91
ETHERLINE Cat.6A + Cat.7	Lapp 2170475	ETHERLINE® Cat.7 P	4 x 2 x AWG22/1	9.0	53.0	91
Outer sheath: PVC						
ETHERLINE Cat.6A + Cat.7	Lapp 2170464	ETHERLINE® Cat.6A Y	4 x 2 x AWG22/1	9.0	53.0	98
ETHERLINE Cat.6A + Cat.7	Lapp 2170474	ETHERLINE® Cat.7 Y	4 x 2 x AWG22/1	9.0	53.0	98