



Description: ETHERLINE TORSION Cat. 5_

Lapp code: Lapp 2170888

The **Test voltage** of the cable Lapp 2170888 is 700 V.

Application range

- Many applications with Industrial Ethernet, e.g. PROFINET, i.e. fixed installation, flexible use as well as TORSION.
- Plant engineering, machinery manufacturing
- suitable for EtherCAT and EtherNet/IP applications

Product Make-up

- Stranded conductor, tinned
- AWG 22 (19-wire)
- PE core insulation
- Star quad
- Screening: wrapped with braided tinned-copper wires
- Non-woven wrapping
- PUR outer sheath, green (RAL 6018)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170888 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | Number of pairs and AWG per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------|--------------|--------------------------|---------------------------------------|---------------------|----------------------|----------------|
| ETHERLINE® TORSION CAT.5 | | | | | | |
| ETHERLINE TORSION Cat. 5 | Lapp 2170888 | ETHERLINE® TORSION CAT.5 | 2 x 2 x AWG22/19 | 6,8 | 31.3 | 52 |