



Description: Field mountable S-A connectors M8_

Lapp code: Lapp 22260044

The **Test voltage** of the cable Lapp 22260044 is /.

Application range

- Automation technology
- Mechanical engineering
- Plant engineering
- Tool shop
- Automotive industry

/

In our Cable list on next page you can find all interesting information acc. article Lapp 22260044 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | Number of pins | Min. conductor cross-section/ flexible/ in mm ² | Max. conductor cross-section/ flexible/ in mm ² | Min. cable diameter (mm) | Max. cable diameter (mm) | Rated voltage (V) | Rated current (A) | PU |
|--|---------------|---------------------|----------------|--|--|--------------------------|--------------------------|-------------------|-------------------|----|
| Straight connector, fast-connect (insulation displacement) | | | | | | | | | | |
| Field mountable S/A connectors M8 | Lapp 22260993 | AB-C3-M8 MS-F0,25 | 3 | 0.08 | 0.25 | 2.5 | 5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260985 | AB-C3-M8 MS-F0,5 | 3 | 0.25 | 0.5 | 2.5 | 5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260043 | AB-C4-M8 MS-F0,25 | 4 | 0.08 | 0.25 | 2.5 | 5 | 30 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260044 | AB-C4-M8 MS-F0,5 | 4 | 0.25 | 0.5 | 2.5 | 5 | 30 | 4 | 1 |
| Straight connector, fast-connect (piercing) | | | | | | | | | | |
| Field mountable S/A connectors M8 | Lapp 22260122 | AB-C3-M8MS-P | 3 | 0.14 | 0.38 | 3 | 5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260123 | AB-C4-M8MS-P | 4 | 0.14 | 0.38 | 3 | 5 | 30 | 4 | 1 |
| Straight connector, screw connection | | | | | | | | | | |
| Field mountable S/A connectors M8 | Lapp 22260120 | AB-C3-M8MS | 3 | 0.14 | 0.5 | 3.5 | 5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260121 | AB-C4-M8MS | 4 | 0.14 | 0.5 | 3.5 | 5 | 30 | 4 | 1 |
| Straight socket, fast-connect (insulation displacement) | | | | | | | | | | |
| Field mountable S/A connectors M8 | Lapp 22260994 | AB-C3-M8F S-F0,25 | 3 | 0.08 | 0.25 | 2.5 | 5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260986 | AB-C3-M8F S-F0,5 | 3 | 0.25 | 0.5 | 2.5 | 5 | 60 | 4 | 1 |

Field mountable S-A connectors M8_

Lapp 22260044



| Product Name | Lapp Nr. | Article designation | Number of pins | Min. conductor c ross-section/ flexible/ in mm ² | Max. conductor c ross-section/ flexible/ in mm ² | Min. cable diameter (mm) | Max. cable diameter (mm) | Rated voltage (V) | Rated current (A) | PU |
|--|---------------|-----------------------|----------------|---|---|--------------------------|--------------------------|-------------------|-------------------|----|
| Field mountable S/A connectors M8 | Lapp 22260045 | AB-C4-M8F S-F0,25 | 4 | 0.08 | 0.25 | 2.5 | 5 | 30 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260046 | AB-C4-M8F S-F0,5 | 4 | 0.25 | 0.5 | 2.5 | 5 | 30 | 4 | 1 |
| Straight socket, fast-connect (piercing) | | | | | | | | | | |
| Field mountable S/A connectors M8 | Lapp 22260124 | AB-C3-M8FS-P | 3 | 0.14 | 0.38 | 3 | 5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260119 | AB-C4-M8FS-P | 4 | 0.14 | 0.38 | 3 | 5 | 30 | 4 | 1 |
| Straight socket, screw connection | | | | | | | | | | |
| Field mountable S/A connectors M8 | Lapp 22260125 | AB-C3-M8FS | 3 | 0.14 | 0.5 | 3.5 | 5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22260126 | AB-C4-M8FS | 4 | 0.14 | 0.5 | 3.5 | 5 | 30 | 4 | 1 |
| Straight connector, shielded, screw connection | | | | | | | | | | |
| Field mountable S/A connectors M8 | Lapp 22262025 | AB-C3-M8 MS-M-0,34-SH | 3 | 0.14 | 0.5 | 3.5 | 5.5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22262027 | AB-C4-M8 MS-M-0,34-SH | 4 | 0.14 | 0.5 | 3.5 | 5 | 30 | 4 | 1 |
| Straight socket, shielded, screw connection | | | | | | | | | | |
| Field mountable S/A connectors M8 | Lapp 22262026 | AB-C3-M8F S-M-0,34-SH | 3 | 0.14 | 0.5 | 3.5 | 5.5 | 60 | 4 | 1 |
| Field mountable S/A connectors M8 | Lapp 22262028 | AB-C4-M8F S-M-0,34-SH | 4 | 0.14 | 0.5 | 3.5 | 5.5 | 30 | 4 | 1 |