



**Description:** Field mountable S-A connectors M8\_

**Lapp code:** Lapp 22260046

The **Test voltage** of the cable Lapp 22260046 is /.

## Application range

- Automation technology
- Mechanical engineering
- Plant engineering
- Tool shop
- Automotive industry

/

In our Cable list on next page you can find all interesting information acc. article Lapp 22260046 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pins	Min. conductor cross-section/ flexible/ in mm <sup>2</sup>	Max. conductor cross-section/ flexible/ in mm <sup>2</sup>	Min. cable diameter (mm)	Max. cable diameter (mm)	Rated voltage (V)	Rated current (A)	PU
Straight connector, fast-connect (insulation displacement)										
Field mountable S/A connectors M8	Lapp 22260993	AB-C3-M8 MS-F0,25	3	0.08	0.25	2.5	5	60	4	1
Field mountable S/A connectors M8	Lapp 22260985	AB-C3-M8 MS-F0,5	3	0.25	0.5	2.5	5	60	4	1
Field mountable S/A connectors M8	Lapp 22260043	AB-C4-M8 MS-F0,25	4	0.08	0.25	2.5	5	30	4	1
Field mountable S/A connectors M8	Lapp 22260044	AB-C4-M8 MS-F0,5	4	0.25	0.5	2.5	5	30	4	1
Straight connector, fast-connect (piercing)										
Field mountable S/A connectors M8	Lapp 22260122	AB-C3-M8MS-P	3	0.14	0.38	3	5	60	4	1
Field mountable S/A connectors M8	Lapp 22260123	AB-C4-M8MS-P	4	0.14	0.38	3	5	30	4	1
Straight connector, screw connection										
Field mountable S/A connectors M8	Lapp 22260120	AB-C3-M8MS	3	0.14	0.5	3.5	5	60	4	1
Field mountable S/A connectors M8	Lapp 22260121	AB-C4-M8MS	4	0.14	0.5	3.5	5	30	4	1
Straight socket, fast-connect (insulation displacement)										
Field mountable S/A connectors M8	Lapp 22260994	AB-C3-M8F S-F0,25	3	0.08	0.25	2.5	5	60	4	1
Field mountable S/A connectors M8	Lapp 22260986	AB-C3-M8F S-F0,5	3	0.25	0.5	2.5	5	60	4	1

# Field mountable S-A connectors M8\_

Lapp 22260046



Product Name	Lapp Nr.	Article designation	Number of pins	Min. conductor cross-section/ flexible/ in mm <sup>2</sup>	Max. conductor cross-section/ flexible/ in mm <sup>2</sup>	Min. cable diameter (mm)	Max. cable diameter (mm)	Rated voltage (V)	Rated current (A)	PU
Field mountable S/A connectors M8	Lapp 22260045	AB-C4-M8F S-F0,25	4	0.08	0.25	2.5	5	30	4	1
Field mountable S/A connectors M8	Lapp 22260046	AB-C4-M8F S-F0,5	4	0.25	0.5	2.5	5	30	4	1
Straight socket, fast-connect (piercing)										
Field mountable S/A connectors M8	Lapp 22260124	AB-C3-M8FS-P	3	0.14	0.38	3	5	60	4	1
Field mountable S/A connectors M8	Lapp 22260119	AB-C4-M8FS-P	4	0.14	0.38	3	5	30	4	1
Straight socket, screw connection										
Field mountable S/A connectors M8	Lapp 22260125	AB-C3-M8FS	3	0.14	0.5	3.5	5	60	4	1
Field mountable S/A connectors M8	Lapp 22260126	AB-C4-M8FS	4	0.14	0.5	3.5	5	30	4	1
Straight connector, shielded, screw connection										
Field mountable S/A connectors M8	Lapp 22262025	AB-C3-M8 MS-M-0,34-SH	3	0.14	0.5	3.5	5.5	60	4	1
Field mountable S/A connectors M8	Lapp 22262027	AB-C4-M8 MS-M-0,34-SH	4	0.14	0.5	3.5	5	30	4	1
Straight socket, shielded, screw connection										
Field mountable S/A connectors M8	Lapp 22262026	AB-C3-M8F S-M-0,34-SH	3	0.14	0.5	3.5	5.5	60	4	1
Field mountable S/A connectors M8	Lapp 22262028	AB-C4-M8F S-M-0,34-SH	4	0.14	0.5	3.5	5.5	30	4	1