



**Description:** H01N2-D 16\_  
**Lapp code:** Lapp 2210700

The **Test voltage** of the cable Lapp 2210700 is 1000 V.

## Application range

- Application standard for H01N2-D: HD 516/VDE 0298-300
- For transmitting high currents from the electric welding device to the welding tool
- Use the welding cable only under consideration of HD 516/VDE 0298-300
- Can be used in dry or damp rooms

## Product Make-up

- Bare copper wire according to HAR
- Stranding approximately corresponds to class 6 up to 95 mm<sup>2</sup>, and from 120 mm<sup>2</sup> approximately to class 5 acc. to VDE 0295
- Separator made of synthetic film or paper
- Outer sheath: rubber compound, type EM5

In our Cable list on next page you can find all interesting information acc. article Lapp 2210700 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm <sup>2</sup> )	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
H01N2-D 10	Lapp 2310026	10	7,7 - 9,7	96.0	171
H01N2-D 16	Lapp 2210700	16	8,8 - 11	153.6	198
H01N2-D 25	Lapp 2210701	25	10,1 - 12,7	240.0	305
H01N2-D 35	Lapp 2210702	35	11,4 - 14,2	336.0	415
H01N2-D 50	Lapp 2210703	50	13,2 - 16,5	480.0	555
H01N2-D 70	Lapp 2210704	70	15,3 - 19,2	672.0	765
H01N2-D 95	Lapp 2210705	95	17,1 - 21,4	912.0	1010
H01N2-D 120	Lapp 2210706	120	19,2 - 24	1152.0	1262
H01N2-D 150	Lapp 2210707	150	21,2 - 26,4	1440.0	1610
H01N2-D 240	Lapp 2210708	240	25 - 29,5	2304.0	2520