



Description: H05RN-F 3 G 0,75_

Lapp code: Lapp 1600252

The **Test voltage** of the cable Lapp 1600252 is 2000 V.

Application range

- According to HD 516/VDE 0298-300: for supplying devices in households, kitchens or offices under light mechanical stress; handheld inspection lamps
- According to HD 516/VDE 0298-300: provided the maximum conductor temperature of +60 °C, the maximum outer sheath surface temperature of +50 °C and the lack of ozone resistance are taken into account, suitable for permanent use outdoors with conventional mechanical stress

Product Make-up

- Bare copper wire according to HAR
- Core insulation: rubber compound type EI 4
- Outer sheath: rubber compound, type EM2

In our Cable list on next page you can find all interesting information acc. article Lapp 1600252 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------|---------------|---|---------------------|----------------------|----------------|
| H05RN-F 2 X 0,75 | Lapp 1600250 | 2 X 0,75 | 5,7 - 7,4 | 14.4 | 80 |
| H05RN-F 3 G 0,75 | Lapp 1600252 | 3 G 0,75 | 6,2 - 8,1 | 21.6 | 95 |
| H05RN-F 4 G 0,75 | Lapp 16002583 | 4 G 0,75 | 6,8 - 8,8 | 28.8 | 105 |
| H05RN-F 2 X 1,0 | Lapp 1600251 | 2 X 1,0 | 6,1 - 8 | 19.2 | 95 |
| H05RN-F 3 G 1,0 | Lapp 1600253 | 3 G 1,0 | 6,5 - 8,5 | 28.8 | 115 |