



Description: H05RR-F 4 G 1,5_
Lapp code: Lapp 16002013

The **Test voltage** of the cable Lapp 16002013 is 2000 V.

Application range

- Handheld and power supply devices according to HD 516
- For lightweight workshop tools that are subject to light loads
- According to HD 516/VDE 0298-300: dry and damp rooms; only temporary use outdoors; not for industrial/commercial or agricultural facilities, except tailors/cutting workshops; not suitable for supplying industrial power tools
- Light & sound technology

Product Make-up

- Bare copper wire according to HAR
- Core insulation: rubber compound type EI 4
- Outer sheath: rubber compound, type EM3

In our Cable list on next page you can find all interesting information acc. article Lapp 16002013 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
H05RR-F 2 X 0,75	Lapp 1600203	2 X 0,75	5,7 - 7,4	14.4	61
H05RR-F 3 G 0,75	Lapp 1600207	3 G 0,75	6,2 - 8,1	21.6	75
H05RR-F 2 X 1,0	Lapp 1600204	2 X 1,0	6,1 - 8	19.2	73
H05RR-F 3 G 1,0	Lapp 1600208	3 G 1,0	6,5 - 8,5	28.8	86
H05RR-F 4 G 1,0	Lapp 16002113	4 G 1,0	7,1 - 9,3	38.4	105
H05RR-F 2 X 1,5	Lapp 1600205	2 X 1,5	7,6 - 9,8	28.8	115
H05RR-F 3 G 1,5	Lapp 1600200	3 G 1,5	8 - 10,4	43.2	135
H05RR-F 4 G 1,5	Lapp 16002013	4 G 1,5	9 - 11,6	57.6	165
H05RR-F 5 G 1,5	Lapp 16002023	5 G 1,5	9,8 - 12,7	72.0	190
H05RR-F 2 X 2,5	Lapp 1600206	2 X 2,5	9 - 11,6	48.0	160
H05RR-F 3 G 2,5	Lapp 1600209	3 G 2,5	9,6 - 12,4	72.0	190
H05RR-F 4 G 2,5	Lapp 16002123	4 G 2,5	10,7 - 13,8	96.0	235
H05RR-F 5 G 2,5	Lapp 16002133	5 G 2,5	11,9 - 15,3	120.0	285