



Description: H07RN8-F 7 G 1,5_

Lapp code: Lapp 1600620

The **Test voltage** of the cable Lapp 1600620 is 2500 V.

Application range

- Dry or damp rooms, as well as outdoors and in industrial water acc. HD 516 and EN 50525-2-21
- For connecting mobile, electrical equipment in industrial water
- For use with submersible pumps

Product Make-up

- Strands of bare copper wires
- Core insulation: rubber compound type EI 4
- Outer sheath: rubber compound, type EM2

In our Cable list on next page you can find all interesting information acc. article Lapp 1600620 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
H07RN8-F 1 X 4	Lapp 1600600	1 X 4	7,2 - 9	38.4	100
H07RN8-F 1 X 6	Lapp 1600601	1 X 6	7,9 - 9,8	57.6	120
H07RN8-F 1 X 10	Lapp 1600602	1 X 10	9,5 - 11,9	96.0	200
H07RN8-F 1 X 25	Lapp 1600604	1 X 25	12,7 - 15,8	240.0	400
H07RN8-F 3 G 1,5	Lapp 1600606	3 G 1,5	9,2 - 11,9	43.2	170
H07RN8-F 4 G 1,5	Lapp 1600609	4 G 1,5	10,2 - 13,1	57.6	205
H07RN8-F 7 G 1,5	Lapp 1600620	7 G 1,5	14 - 17,5	100.8	385
H07RN8-F 3 G 2,5	Lapp 1600607	3 G 2,5	10,9 - 14	72.0	210
H07RN8-F 4 G 2,5	Lapp 1600610	4 G 2,5	12,1 - 15,5	96.0	260
H07RN8-F 7 G 2,5	Lapp 1600621	7 G 2,5	16,5 - 20	168.0	520
H07RN8-F 4 G 4	Lapp 1600611	4 G 4	14 - 17,9	153.6	356
H07RN8-F 4 G 6	Lapp 1600612	4 G 6	15,7 - 20	230.4	475
H07RN8-F 4 G 10	Lapp 1600613	4 G 10	20,9 - 26,5	384.0	837
H07RN8-F 4 G 16	Lapp 1600614	4 G 16	23,8 - 30,1	614.4	1220
H07RN8-F 4 G 25	Lapp 1600615	4 G 25	28,9 - 36,6	960.0	1770
H07RN8-F 4 G 35	Lapp 1600616	4 G 35	32,5 - 41,1	1344.0	2304