



Description: H07ZZ-F 3 G 2,5_
Lapp code: Lapp 1600820

The **Test voltage** of the cable Lapp 1600820 is 2500 V.

Application range

- Stage technology
- For mobile equipment and machines
- Dry or damp rooms, as well as outdoors acc. to HD 516/VDE 0298-300
- For buildings or industrial plants with a high density of people or valuable assets
- Similar product: H07RN-F, enhanced version

Product Make-up

- Strands of bare copper wires
- Core insulation: Halogen-free rubber compound
- Outer sheath: rubber compound, halogen-free

In our Cable list on next page you can find all interesting information acc. article Lapp 1600820 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
H07ZZ-F 3 G 1,5	Lapp 1600810	3 G 1,5	9,2 - 11,9	43.2	125
H07ZZ-F 4 G 1,5	Lapp 1600811	4 G 1,5	10,2 - 13,1	57.6	155
H07ZZ-F 5 G 1,5	Lapp 1600812	5 G 1,5	11,2 - 14,4	72.0	190
H07ZZ-F 14 G 1,5	Lapp 1600815	14 G 1,5	18,8 - 21,3	201.6	570
H07ZZ-F 18 G 1,5	Lapp 1600816	18 G 1,5	20,7 - 26,3	259.2	750
H07ZZ-F 3 G 2,5	Lapp 1600820	3 G 2,5	10,9 - 14	72.0	185
H07ZZ-F 4 G 2,5	Lapp 1600821	4 G 2,5	12,1 - 15,5	96.0	235
H07ZZ-F 5 G 2,5	Lapp 1600822	5 G 2,5	13,3 - 17	120.0	290
H07ZZ-F 7 G 2,5	Lapp 1600823	7 G 2,5	18,2 - 20,7	168.0	520
H07ZZ-F 14 G 2,5	Lapp 1600825	14 G 2,5	22,2 - 25	336.0	860
H07ZZ-F 4 G 4	Lapp 1600836	4 G 4	14 - 17,9	153.6	325
H07ZZ-F 5 G 4	Lapp 1600837	5 G 4	15,6 - 19,9	192.0	410
H07ZZ-F 4 G 6	Lapp 1600841	4 G 6	15,7 - 20	230.4	440
H07ZZ-F 5 G 6	Lapp 1600842	5 G 6	17,5 - 22,2	288.0	550
H07ZZ-F 4 G 10	Lapp 1600844	4 G 10	20,9 - 26,5	384.0	770
H07ZZ-F 5 G 10	Lapp 1600845	5 G 10	22,9 - 29,1	480.0	950
H07ZZ-F 4 G 16	Lapp 1600847	4 G 16	23,8 - 30,1	614.4	1070
H07ZZ-F 4 G 25	Lapp 1600849	4 G 25	28,9 - 36,6	960.0	1570
H07ZZ-F 4 G 35	Lapp 1600851	4 G 35	32,5 - 41,1	1344.0	2040
H07ZZ-F 4 G 50	Lapp 1600852	4 G 50	37,7 - 47,5	1920.0	2810